

tesa® Powerstrips Waterproof Duo Hook metal-plastic



Product Information

BNR 59785

Product Features

- · Easy to mount without drilling, screws or nails
- · Strong hold up to 3kg
- Removable without a trace due to the Powerstrips Waterproof technology
- Material combination stainless steel & plastic
- Usable on tiles, glass, etc. in humid rooms or directly in the shower*
- Especially developed for wet areas (e.g. shower, bath tub etc.)
- · Ideal to hold e.g. a sponge, washrag, etc. if needed in the shower
- · Reusable with tesa Powerstrips Waterproof Large

Application Fields

How to apply:

- 1. Clean the surface with alcohol or silicone-free glass cleaner
- 2. Take the included waterproof primer tissue and wipe over the surface for bonding preparation wait for 10 seconds minimum
- 3. Apply the Powerstrip Waterproof Large strips on the surface press for 5 seconds minimum
- 4. Disengage the base plate of the hook and stick it onto the strips press for 5 seconds minimum
- 5. Let the hook slide down on the base plate until it is locked

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Application temperature

•	Type of adhesive	synthetic rubber	•	Hook shape	Rectangular
	Holding power up to	3 Ka			

Properties/Performance Values

	i ile le construction de configuration de				,
•	Applicationfield	Bathroom, Kitchen	•	Reusable	yes
•	Chemical resistance	no	•	Reusable with	Powerstrips
•	Hazard material	yes			Waterproof Large
•	Material	Stainless steel, Plastic	•	Solvent free	yes
•	Oil and grease resistance	no	•	Temperature resistance	yes
•	Ozone resistance	no	•	UV resistant	no

from 15° up to 35° °C • Residue free removal

ves

^{*}Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material



tesa® Powerstrips Waterproof Duo Hook metal-plastic

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.